

8365W-267

1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



KEY FEATURES

VALUE
Package

CONSISTENT AND DEPENDABLE
Operation

WI-FI
Built In

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®

Turns on garage door opener lights from inside the garage.



882LMW

(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ Light Accessories each.



893LM

WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



825LM

REMOTE LIGHT SWITCH

Replaces an existing wall switch to enable home lighting control with a garage remote or smartphone.



823LM

DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS.

SECURE

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MyQ TECHNOLOGY ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

PRODUCT GUIDE 8365W-267

1/2 HP AC CHAIN DRIVE WI-FI
GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR



- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS



- Steel Chassis, T-Rail and Trolley
- Full Chain Drive Mechanism (16:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- AC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)

7.25"



18.25"

10.5"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	10'	10'

Headroom Clearance Required: 2"

7"

Per second
for door
to move
upward

SPEED

7"

Per second
for door
to move
downward

STANDARD SPECS.

SECURITY

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -35°F to 150°F

SECURITY+ 2.0®

- (2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)
- Remote Controls: 310, 315 and 390 MHz Tri-Band*
- Keyless Entry: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only.

ENCRYPTED CONTROLS

- Multi-Function Control Panel® (882LMW)
- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delay
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8365W)
- Multi-Function Control Panel (882LMW)
- (2) 3-Button Remote Controls (893LM)
- Wireless Keyless Entry (877LM)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices

